

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH FLUXCAKE-301 (CW-301)

MSDS Number: MSDS-CW 4327 Revised Date: 24 JUNE 2011

Product Use: Industrial Use - Flux cored wire for soldering applications. (See alloy table for metal alloy mix)

MANUFACTURER:

In America: EMERGENCY PHONE:
The Indium Corporation of America CHEMTREC 24 hrs

The Indium Corporation of America CHEMTREC 24 hrs. 1676 Lincoln Ave., Utica NY 13502 USA: 1 (800) 424-9300

Information: (315) 853-4900 Outside USA: +1 (703) 527-3887 nswarts@indium.com

Indium Corporation of America Chicago Materials Division 80 Scott Street

Elk Grove Village, Illinois 60007

Information: +65 6268-8678

In Europe: In China:

Indium Corporation of Europe
7 Newmarket Ct.
Indium Corporation (Suzhou), Co., Ltd.
No. 428 Xinglong Street

Kingston, Milton Keynes, UK, MK 10 OAG

Suzhou Industrial Park
Information: +44 [0] 1908 580400

Suzhou Industrial Square

Unit No. 14-C

In Asia:

Jiangsu Province, China 215126

Asia-Pacific Operations-Singapore Information: (86) 512-6283-4900 29 Kian Teck Avenue Singapore 628908

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Carcinogen listed in

⊕Eye ⊕Inhalation ⊕Skin ⊕Ingestion NTP IARC OSHA ⊕Not Listed

GHS:







lead/antimony containing products only

Signal Word: Warning

Hazard statement(s)

H302 Harmful if swallowed H320 Causes eye irritation

H335 May cause respiratory irritation
H351 Suspected of causing cancer (lead)

H360 May damage fertility or the unborn child (applicable to lead containing product)

H373 May cause damage to organs through prolonged or repeated exposure (applicable to lead containing

product)

H400+H413 Very toxic to aquatic life, may cause long lasting harmful effects to aquatic life (lead/antimony containing

products)

EUH201A Warning! Contains lead (applicable only to the products listed that contain lead) Review listing.

Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes

POTENTIAL HEALTH EFFECTS:

Eye Contact: Irritating to the eyes and if not removed, may result in serious injury. Contact with fume

from molten metal may cause irritation.

Ingestion: This product contains metal and organic chemicals. This product may contain

lead. Harmful if swallowed. When applicable, may cause systematic lead poisoning. Symptoms of lead poisoning include headache, nausea, abdominal pain, muscle and joint pain and damage to the

nervous system, blood system and kidneys.

Inhalation: Inhalation of fume or dust may cause local irritation to the respiratory system. Inhalation of lead fume

may be harmful.

Skin Contact: May cause skin irritation.

Chronic: SILVER: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition

known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Prolonged inhalation of fume may result in lung complications.

<u>COPPER:</u> Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin

and hair.

LEAD: Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory

irritation and systematic lead poisoning.

<u>INDIUM:</u> May cause damage to respiratory system. Kidney and liver damage from injection of indium compounds has been reported based on limited animal testing. Target organs: teeth and

gums.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its products

for human consumption.

WARNING: Applicable within the State of California Only - This product contains chemicals known to the State of

California to cause cancer and birth defects or other reproductive harm. (lead).

WARNING: This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use

of leaded solders in making of joints in any private or public potable (drinking) water supply system.

Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components % wt CAS Registry #/EINECS# PEL TLV-TWA TLV-STEL mg/m³ mg/m³ mg/m³

TIN * 7440-31-5/231-141-8

MSDS - CW 4327		INDAL	LOY WITH FLUXCAK	E-301 (CW-301) I
	(US)	2	2	-
	(EU)	-	2	4
	(Canada)	-	2	4
	(Singapore)	2	-	-
	* 7440 00 4/004 404 0			
SILVER	* 7440-22-4/231-131-3 (US)	0.01	0.1	_
	(EU)	-	0.1	_
	(Canada)	_	0.1	0.3
	(Singapore)	0.1	-	-
	(Mexico)	-	0.1	_
COPPER	* 7440-50-8/231-159-6		0.1	
33 En	(US)	0.1 (fume)	0.2 (fume)	-
	(EU)		0.2 (fume)	_
	(Canada)	_	0.2 (fume)	0.6 (fume)
	(Singapore)	0.2(fume)	0.2 (lume) -	o.o (lume)
	(Mexico)	- -	0.2(fume)	2
	(China)	_	0.2(fume)	0.6
	(Orinia)		0.2(lulle)	0.0
LEAD	* 7439-92-1/231-100-4			
	(US)	0.05	0.05	-
	(EU)	-	0.15	-
	(Canada)	0.05	0.05	-
	(Singapore)	0.15		
			-	-
	(Mexico)	N.E.	0.15	-
	(China)	-	0.05(dust)	-
		0.03(fume)	-	
INDIUM	* 7440-74-6/231-180-0			
	(US)	0.1	0.1	-
	(EU)	-	0.1	0.3
	(Canada)	-	0.1	0.3
	(Singapore)	0.1	-	-
	(Mexico)	0.1	-	0.3
	(China)	0.1	-	0.3

ANTIMONY	*	7440-36-0/231-146-5			
		(US)	0.5	0.5	-
		(EU)	0.5	-	-
		(Canada)	-	0.5	1.5
		(Mexico)	N.E.	0.5	-
		(Singapore)	0.5	-	-
		(China)	-	0.5	<u> </u>
RESIN MIX	4.0-6.0	-	N.E.	N.E.	N.E.

PRODUCT DOES NOT CONTAIN ANY REPORTABLE EU SUBSTANES OF VERY HIGH CONCERN (SVHC)

N.E. = Not established

ALLOY TABLE

Metal alloy mixed with resin core (1-5%)

INDALLOY	Lead Pb	Tin Sn	Copper Cu	Antimony Sb	Silver Ag	Indium In	Specific Gravity	RoHS Compliance
104 (Sn62/Pb36/Ag2)	34-35.6	58.9-61	-	-	1.9-1.98	-	8.41	No
106 (Sn63/Pb37)	35-36.6	60-62	-	-	-	-	8.40	No
227 (77.2Sn/20ln/2.8Ag)	-	73.3-76.4	-	-	2.66-2.77	19-19.8	7.25	Yes
254 (86.7Sn/10In/3.1Ag)	-	82.3-85.8	-	-	2.9-3	9.5-9.9	7.37	Yes
256 (SAC 305) (96.5Sn/3Ag/0.5Cu)	-	91.6-95.5	0.475-0.495	-	2.85-2.97	-	7.40	Yes
Sn 995 (99.5Sn/0.5Cu/<50ppm Co)	-	94.5-98.5	0.475-0.495	-	-	-	7.29	Yes
NON STANDARD ALLOY (96.35Sn/3Ag/0.5Cu/0.15Sb)	-	91.5 - 95.4	0.475-0.495	0.14-0.149	2.85-2.97	-	7.35	Yes

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

^{*} See alloy table

MSDS - CW 4327

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. Method: Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established.

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Firefighters must wear NIOSH approved self-contained breathing apparatus and full

Procedures: protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Pick up solids and put in container for reuse or recycling. Do not sweep powder or

small particulate. Use vacuum. Reduce airborne dust and prevent scattering by moistening with water. Dispose of following all Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills.

Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes

until hands are washed.

Storage Precautions: Refer to product label for specific storage temperature requirements. Rotate stock to ensure

use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Local exhaust ventilation is recommended to keep exposures below established limits and

protect operators. Use proper ventilation when working with leaded products.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended under certain circumstances where airborne concentrations are expected

to be elevated or exceed exposure limits.

Skin: Compatible chemical resistant gloves may be required for certain applications. Hot gloves as needed

for melting applications.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

Follow standard lead work practices when working with lead containing products.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential.

Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water

immediately upon leaving the work area. Follow applicable lead work practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Solid metal wire Not applicable. Appearance: **Boiling Point:** Odor: Odorless **Melting Point:** See table **Specific Gravity:** See table pH: Not applicable **Vapor Pressure:** Not established Solubility in Water: Insoluble

Vapor Density: (air=1) Not applicable.

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Not established.

Incompatible Materials: Avoid contact with acids, bases or oxidizing agents.

Hazardous Decomposition / Harmful organic fumes and toxic oxide fumes may form at elevated

Combustion: temperatures.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

OSHA: No

IARC: Yes Lead and lead compounds are listed as possible carcinogens.

LD50: Not established. **LC50:** Not established.

Chronic Toxicity: Lead can cause potential harm to the developing fetus.

12. ECOLOGICAL INFORMATION

This section is subject to future development.

Protect not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for

recycling. Otherwise, dispose of in accordance with all Federal, State and Local

environmental regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States

Department of Transportation.

Not hazardous under shipping regulations.

UN - none

15. REGULATORY INFORMATION

The information in this Material Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace, GBZ2-2002.

This product has been classified in accordance with the Mexican regulations NOM-018-STPS-2000 and NOM-010-STPS-1999.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).



Canadian WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic). (lead)

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

SARA 313 Listing - 40 CFR 372.65 Silver Copper Lead

All ingredients are listed on the EPA TSCA Inventory.

EPA Genetic Toxicology Program - Lead CAS# 7439-92-1

Applicable only in the State of California - California Prop 65 Safe Drinking Water Standard: Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (listed metals)

EC Classification, Packaging and Labeling Requirements:

Symbol and Hazard Classification of Product



Risk Phrases:

R20/22 Harmful by inhalation and if swallowed
R36/37/38 Irritating to eyes, respiratory system and skin

R33 Danger of cumulative effects (lead)

R40 Limited evidence of carcinogenic effect (lead)

R48 Danger of serious damage to health by prolonged exposure (lead)

R50/53 Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment (lead)

R61 May cause harm to the unborn child (lead)

Safety Phrases:

MSDS -	CM	1227
NI2112 -	- (,///	4.3//

S20/21	When using do not eat, drink or smoke
S23	Do not breathe fumes
S24/25	Avoid contact with skin and eyes
S28	After contact with skin wash immediately with plenty of soap and water
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection
S62	If swallowed, do not induce vomiting seek medical advice immediately and show container or label
S7	Keep container tightly closed

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 1 Reactivity: 0

Revised Date: 24 JUNE 2011

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.