

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: INDALLOY WITH FLUXCAKE-301 (CW-301)

SDS Number: SDS-CW 4327 Revised Date: 2 NOVEMBER 2016

Product Use: Industrial Use - Flux cored wire for soldering applications. (See alloy table for metal alloy mix)

MANUFACTURER:

In America: EMERGENCY PHONE:

The Indium Corporation of America

1676 Lincoln Ave., Utica NY 13502

Information: (315) 853-4900

CHEMTREC 24 hrs.

USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

Information: (315) 853-4900 nswarts@indium.com

Indium Corporation of America Chicago Materials Division 80 Scott Street Elk Grove Village, Illinois 60007

In Europe:

Indium Corporation of Europe

7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG

Information: +44 [0] 1908 580400

In Asia:

The Indium Corporation of America

Asia-Pacific Operations-Singapore

29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678

In China:

Indium Corporation (Suzhou), Co., Ltd.

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Carcinogen listed in

⊕Eye ⊕Inhalation ⊕Skin ⊕Ingestion NTP IARC OSHA ⊕Not Listed

GHS:







lead containing products only

Signal Word: Warning Hazard statement(s)

H303 May be harmful if swallowed (lead)
H335 May cause respiratory irritation
H351 Suspected of causing cancer (lead)

H361 Suspected of damaging fertility or the unborn child (applicable to lead containing product)

H373 May cause damage to organs through prolonged or repeated exposure (applicable to lead containing

product)

H410 Very toxic to aquatic life with long lasting effects (lead containing products)

EUH201A Warning! Contains lead (applicable only to the products listed that contain lead) Review listing.

Precautionary statement(s)

P233 Keep container tightly closed

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 + P364 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 +P 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + P351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

P501 Dispose of contents and containers following applicable regulations.

Classification:

Acute toxicity, - Category 4 (lead)

Specific target organ toxicity- repeated exposure - Category 2

Carcinogenicity (Category 2) (lead)

Reproductive toxicity (Category 2) (lead)

Acute aguatic toxicity – Category 1 for lead containing products (H400)

Chronic aquatic toxicity – Category 1 for lead containing products(H410)

POTENTIAL HEALTH EFFECTS:

Eye Contact: Irritating to the eyes and if not removed, may result in serious injury. Contact with fume from molten metal may cause irritation.

Ingestion: This product contains metal and organic chemicals.

Inhalation: Inhalation of fume or dust may cause local irritation to the respiratory system. Inhalation of lead fume

may be harmful.

Skin Contact: May cause skin irritation.

Chronic:

<u>SILVER</u>: Chronic skin contact or ingestion of silver powder, salts or fume can result in a condition known as Argyria, a condition with bluish pigmentation of the skin and eyes.

TIN: Prolonged inhalation of fume may result in lung complications.

<u>COPPER:</u> Overexposure to fumes of copper may cause metal fume fever (chills, muscle aches, nausea, fever; dry throat, cough, weakness, lassitude); metallic or sweet taste; discoloration of skin and hair.

<u>LEAD:</u> Prolonged exposure to vapors or fumes at higher temperatures may cause respiratory irritation and systematic lead poisoning.

<u>INDIUM:</u> May cause damage to respiratory system. Kidney and liver damage from injection of indium compounds has been reported based on limited animal testing. Target organs: teeth and gums.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its products for human consumption.

WARNING: Applicable within the State of California Only - This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (lead).

WARNING: This product may contain lead. Lead may be harmful to your health. US Federal law prohibits the use of leaded solders in making of joints in any private or public potable (drinking) water supply system. Keep out of the reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS								
Components	% wt	CAS Registry #/EINECS#	CAS Registry #/EINECS# PEL TLV-TWA mg/m³ mg/m³		TLV-STEL mg/m³			
TIN	*	7440-31-5/231-141-8						
		(US)	2	2	-			
		(EU)	-	2	4			
		(Canada)	-	2	4			
		(Singapore)	2	-	-			
SILVER	*	7440-22-4/231-131-3						
		(US)	0.01	0.1	-			
		(EU)	-	0.1	-			
		(Canada)	-	0.1	0.3			
		(Singapore)	0.1	-	-			
		(Mexico)	-	0.1	-			
COPPER	*	7440-50-8/231-159-6						
		(US)	0.1 (fume)	0.2 (fume)	-			

S – CW 4327		INDALL	INDALLOY WITH FLUXCAKE-301 (CW-301) I			
	(EU)	-	0.2 (fume)	-		
	(Canada)	-	0.2 (fume)	0.6 (fume)		
	(Singapore)	0.2(fume)	-	-		
	(Mexico)	-	0.2(fume)	2		
	(China)	-	0.2(fume)	0.6		
LEAD	* 7439-92-1/231-100-4					
	(US)	0.05	0.05	-		
	(EU)	-	0.15	-		
	(Canada)	0.05	0.05	-		
	(Singapore)	0.15	-	-		
	(Mexico)	N.E.	0.15	-		
	(China)	-	0.05(dust)	-		
		0.03(fume)	-			
INDIUM	* 7440-74-6/231-180-0					
	(US)	0.1	0.1	-		
	(EU)	-	0.1	0.3		
	(Canada)	-	0.1	0.3		
	(Singapore)	0.1	-	-		
	(Mexico)	0.1	-	0.3		
	(China)	0.1	-	0.3		
ANTIMONY	* 7440-36-0/231-146-5					
	(US)	0.5	0.5	-		
	(EU)	0.5	-	-		
	(Canada)	-	0.5	1.5		
	(Mexico)	N.E.	0.5	-		
	(Singapore)	0.5	-	-		
	(China)		0.5	<u>-</u>		
RESIN MIX	1.0-5.0	N.E.	N.E.	N.E.		
N.E. = Not estab	olished * See alloy tab	ble				

ALLOY TABLE

Metal alloy mixed with resin core (1-5%)

INDALLOY	Lead Pb	Tin Sn	Copper Cu	Antimony Sb	Silver Ag	Indium In	Specific Gravity	RoHS 2 Compliance
104 (Sn62/Pb36/Ag2)	34-35.6	58.9-61	-	-	1.9-1.98	-	8.41	No
106 (Sn63/Pb37)	35-36.6	60-62	-	-	-	-	8.40	No
133 (Sn95/5Sb)	-	90.3-94	-	4.75-4.95	-	-	7.25	Yes
153 Pb85/Sn15	80.8-84	14.3-14.9	-	-	-	-	10.7	Yes*
227 (77.2Sn/20ln/2.8Ag)	-	73.3-76.4	-	-	2.66-2.77	19-19.8	7.25	Yes
228 (88Pb/10Sn/2Ag)	83.6 - 87	9.5 - 9.9	-	-	1.9 – 1.98	-	10.75	Yes*
241 (SAC387) (95.5Sn/3.8Ag/0.7Cu)	-	90.7 - 94.5	0.67 - 0.69	-	3.6 - 3.76	-	7.4	Yes
254 (86.7Sn/10In/3.1Ag)	-	82.3-85.8	-	-	2.9-3	9.5-9.9	7.37	Yes
256 (SAC 305) (96.5Sn/3Ag/0.5Cu)	-	91.6-95.5	0.475-0.495	-	2.85-2.97	-	7.40	Yes
Sn 995 (99.5Sn/0.5Cu/<50ppm Co)	-	94.5-98.5	0.475-0.495	-	-	-	7.29	Yes
NON STANDARD ALLOY (96.35Sn/3Ag/0.5Cu/0.15Sb)	-	91.5 - 95.4	0.475-0.495	0.14-0.149	2.85-2.97	-	7.35	Yes

^{*}Review RoHS exemptions (2011/65/EU)

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel. Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: Not established. Method: Not established.

Auto-ignition Temperature: Not established.

Flammable Limits: Limits not established.

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Procedures: Firefighters must wear NIOSH approved self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Pick up solids and put in container for reuse or recycling. Do not sweep powder or small particulate. Use vacuum. Reduce airborne dust and prevent scattering by moistening with water. Dispose of following all Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Keep containers tightly closed when not in use. Use care to avoid spills. Always thoroughly wash your hands after handling this product. DO NOT touch or rub eyes until hands are washed.

Storage Precautions: Refer to product label for specific storage temperature requirements. Rotate stock to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Local exhaust ventilation is recommended to keep exposures below established limits and protect operators. Use proper ventilation when working with leaded products.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An approved or compliant marked air-purifying respirator with a fume/organic chemical cartridge is recommended under certain circumstances where airborne concentrations are expected to be elevated or exceed exposure limits.

Skin: Compatible chemical resistant gloves may be required for certain applications. Hot gloves as needed for melting applications.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas. Follow standard lead work practices when working with lead containing products.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately. Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area. Follow applicable lead work practices.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Solid metal wire **Boiling Point:** Not applicable. Odor: Odorless **Melting Point:** See table **Specific Gravity:** See table pH: Not applicable Vapor Pressure: Not established Solubility in Water: Insoluble

Vapor Density: (air=1) Not applicable.

SDS - CW 4327

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Not established.

Incompatible Materials: Avoid contact with acids, bases or oxidizing agents.

Hazardous Decomposition / Combustion: Harmful organic fumes and toxic oxide fumes may form at elevated

temperatures.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

OSHA: No

IARC: Yes Lead and lead compounds are listed as possible carcinogens.

LD50: Not established. **LC50:** Not established.

Chronic Toxicity: Lead can cause potential harm to the developing fetus.

12. ECOLOGICAL INFORMATION

Protect not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Scrap metal alloy usually has value. Contact a commercial reclaimer for recycling. Otherwise, dispose of in accordance with all Federal, State and Local environmental regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements. Not regulated under US DOT (United States Department of Transportation.

Not hazardous under shipping regulations (GROUND/IATA/OCEAN).

UN - none

Marine Pollutant: No

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

SARA 313 Listing - 40 CFR 372.65

Silver Copper Lead

All ingredients are listed on the EPA TSCA Inventory.

EPA Genetic Toxicology Program - Lead CAS# 7439-92-1

Applicable only in the State of California - California Prop 65 Safe Drinking Water Standard: Warning: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (lead)

This product has been classified in accordance with the Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

(Ţ)

Canadian WHMIS: D2A-Materials Causing Other Toxic Effects-Very Toxic Material (Chronic). (lead)

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products

GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agents in the Workplace GBZ2-2007.

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

16. OTHER INFORMATION

Revised Date:

HMIS Hazard Rating: Health: 2

Fire: 1
Reactivity: 0
2 NOVEMBER 2016

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.